

UTILITY PATENT APPLICATION TRANSMITTAL Only for new nonprovisional applications under 37 CFR 1.53(b))		Attorney Docket No. 990377	Total Pages
Check Box, if applicable <input type="checkbox"/> Duplicate		First Named Inventor or Application Identifier	
		Takahiro MATSUMURA	
		Express Mail Label No.	
APPLICATION ELEMENTS FOR: TELEPHONE SET IDENTIFYING METHOD, TELEPHONE SET TYPE IDENTIFYING APPARATUS, PROCESSING APPARATUS AND STORAGE MEDIUM		ADDRESS TO: Assistant Commissioner for Patents BOX PATENT APPLICATIONS Washington, D.C. 20231	

1. ☒ Fee Transmittal Form (Incorporated within this form)
 (Submit an original and a duplicate for fee processing)

2. ☒ Specification Total Pages [36]

3. ☒ Drawing(s) (35 USC 113) Total Sheets [21]

4. ☒ Oath or Declaration Total Pages [5]
 - a. ☒ Newly executed (original)
 - b. ☐ Copy from prior application (37 CFR 1.63(d))
 (for continuation/divisional with Box 17 completed).
 - i. ☐ Deletion of Inventor(s)
 Signed statement attached deleting inventor(s) named in prior application, see 37 CFR 1.63(d)(2) and 1.33(b).

5. ☐ Incorporation by reference (useable if box 4b is checked)
 The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.

6. ☐ Microfiche Computer Program (Appendix)

7. ☐ Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
 - a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement Verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

8. ☒ Assignment Papers (cover sheet and document)

9. ☐ 37 CFR 3.73(b) Statement (when there is an assignee) ☒ Power of Attorney

**UTILITY PATENT
APPLICATION TRANSMITTAL**

(Only for new nonprovisional applications
under 37 CFR 1.53(b))

Attorney Docket No. 990377

First Named Inventor or Application Identifier

Takahiro MATSUMURA

PAGE 2 OF 3

10. ☐ English translation Document (if applicable)

11. ☒ Information Disclosure Statement ☒ Copy of IDS Citation

12. ☐ Preliminary Amendment

13. ☒ Return Receipt Postcard (MPEP 503)

14. ☐ Small Entity Statement(s) ☐ Statement filed in prior application
Status still proper and desired.

15. ☒ Claim for Convention Priority ☒ Certified copy of Priority Document (1)

a. Priority of _____ application no. _____ filed on _____ is claimed under 35 USC 119.
The certified copies/copy have/has been filed in prior application Serial No. _____.
(For Continuing Applications, if applicable).

16. ☐ Other _____

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

☐ Continuation ☐ Division ☐ Continuation-in-part (CIP) of prior application no. ____/____

FEE TRANSMITTAL	Number Filed	Number Extra	Rate	Basic Fee
The filing fee is calculated below				\$760.00
Total Claims	15 - 20		x \$18.00	
Independent Claims	13 - 3	10	x \$78.00	\$780.00
Multiple Dependent Claims			\$260.00	
Basic Filing Fee				\$1540.00
Reduction by 1/2 for small entity				
Fee for recording enclosed Assignment			\$40.00	\$40.00
TOTAL				\$1580.00

DWH/tmb

**UTILITY PATENT
APPLICATION TRANSMITTAL**

(Only for new nonprovisional applications
under 37 CFR 1.53(b))

Attorney Docket No.

990377

First Named Inventor or Application Identifier

Takahiro MATSUMURA

PAGE 3 OF 3

☒ [XX] A check in the amount of \$1,580.00 is enclosed to cover the filing fee of \$1,540.00 and the assignment recordation fee of \$40.00.

☐ [] Please charge our Deposit Account No. **01-2340** in the total amount of _____ to cover the filing fee and the _____ assignment recordation fee. A duplicate of this sheet is attached.

☒ [XX] The Commissioner is hereby authorized to charge payment for any additional filing fees required under 37 CFR 1.16 or credit any overpayment to Deposit Account No. **01-2340**. A duplicate of this sheet is attached.

18. CORRESPONDENCE ADDRESS


ARMSTRONG, WESTERMAN, HATTORI
McLELAND & NAUGHTON
1725 K Street, N.W. Suite 1000
Washington, D.C. 20006
Telephone: (202) 659-2930
Facsimile: (202) 887-0357

SUBMITTED BY

Typed or Printed Name Donald W. Hanson

Reg. No. 27,133

Signature



Date: March 30, 1999

DWH/tmb

SPECIFICATION

TO ALL WHOM IT MAY CONCERN:

BE IT KNOWN THAT I, Takahiro Matsumura, a citizen of Japan residing at Kawasaki-shi, Kanagawa, Japan have invented certain new and useful improvements in

TELEPHONE SET IDENTIFYING METHOD, TELEPHONE SET TYPE
IDENTIFYING APPARATUS, PROCESSING APPARATUS AND STORAGE
MEDIUM

of which the following is a specification : -

TITLE OF THE INVENTION

5 TELEPHONE SET IDENTIFYING METHOD,
 TELEPHONE SET TYPE IDENTIFYING
 APPARATUS, PROCESSING APPARATUS AND
 STORAGE MEDIUM

BACKGROUND OF THE INVENTION

1. Technical Field of the Invention

10 The present invention generally relates to
 telephone set identifying methods, telephone set
 type identifying apparatuses, processing apparatuses
 and storage mediums, and more particularly to a
 telephone set identifying method and a telephone set
15 type identifying apparatus for identifying a type of
 a portable telephone set such as a mobile telephone
 set and a personal handy-phone system (hereinafter
 simply referred to as PHS) telephone set which is
 coupled to a data processing apparatus such as a
20 personal computer and for notifying the identified
 type to the data processing apparatus, a processing
 apparatus, and to a computer-readable storage medium
 which stores a program for causing a computer which
 couples the data processing apparatus to the
25 portable telephone set to identify the type of the
 portable telephone set.

 In this specification, portable telephones
 capable of making a communication while moving will
 be referred to as mobile telephone sets, as opposed
 to PHS telephone sets which are not suited for
30 making a communication while moving.

2. Description of the Related Art

 Recently, the use of portable telephone
 sets such as mobile telephone sets and PHS telephone
 sets have become popular. With the popular use of
35 the portable telephone sets, it has also become
 popular to make a data communication using the
 portable telephone set. However, when viewed from a

data processing apparatus such as a personal
computer (hereinafter also referred to as PC), a
data circuit equipment (DCE) which can be controlled
is designed for a connection system and a
5 communication protocol which are completely
different depending on the portable telephone set
which is coupled to the DCE.

In other words, conventionally, the DCE is
designed depending on the type of portable telephone
10 set to which the personal computer is coupled. For
this reason, when connecting the mobile telephone
set, it is necessary to couple a DCE which is
designed for the connection system and the
communication protocol of the mobile telephone set
15 the personal computer and the mobile telephone set.
On the other hand, when connecting the PHS telephone
set, it is necessary to couple a DCE which is
designed for the connection system and the
communication protocol of the PHS telephone set
20 between the personal computer and the PHS telephone
set.

Conventionally, it is thus necessary to
design and manufacture the DCE exclusively for each
type of portable telephone set. For this reason,
25 there was a problem in that the DCEs cannot be
manufactured at a low cost.

In addition, there was another problem in
that a troublesome operation is required by the user
and that a load on the user is large, because of the
30 need to connect the DCE which is designed
exclusively for the type of portable telephone set
which is to be coupled to the personal computer,
every time a data communication or the like is
carried out using the personal computer. More
35 particularly, in a case where the DCE is mounted on
a PC card or the like, it was necessary to insert
and connect with respect to the personal computer a

PC card which is completely different between a case where the mobile telephone set is coupled to the personal computer and a case where the PHS telephone set is coupled to the personal computer.

5

SUMMARY OF THE INVENTION

Accordingly, it is a general object of the present invention to provide a novel and useful telephone set identifying method, telephone set type
10 identifying apparatus and recording medium, in which the problems described above are eliminated.

Another and more specific object of the present invention to provide a telephone set identifying method, telephone set type identifying
15 apparatus and recording medium, which are capable automatically identifying the type of portable telephone set which is coupled to the data processing apparatus, so that the user does not need to be aware of the type of portable telephone set
20 being coupled, and to realize an inexpensive DCE by making it possible to use a DCE having the same construction regardless of the type of the portable telephone set and to eliminate the need for a troublesome operation by the user so as to greatly
25 reduce the load on the user.

Still another object of the present invention is to provide a telephone set identifying method for identifying a type of portable telephone set to which a data processing apparatus is coupled,
30 comprising the steps of identifying the type of the portable telephone set based on a response with respect to an operation start signal which is output to a data interface part of the portable telephone set. In this case, it is possible to positively
35 identify the type of the portable telephone set being coupled.

A further object of the present invention

is to provide a telephone set identifying method for identifying a type of portable telephone set to which a data processing apparatus is coupled, comprising the steps of identifying the type of the portable telephone set based on a waveform of a signal output from a specific terminal of a data interface part of the portable telephone set. In this case, it is possible to positively identify the type of the portable telephone set immediately when the portable telephone set outputs a synchronizing signal.

Another object of the present invention is to provide a telephone set identifying method for identifying a type of portable telephone set to which a data processing apparatus is coupled, comprising the steps of identifying the type of the portable telephone set based on an allocation pattern of input and output terminals of a data interface part of the portable telephone set. In this case, it is possible to positively identify the type of the portable telephone set immediately when the portable telephone set is coupled.

Still another object of the present invention is to provide a telephone set type identifying apparatus for identifying a type of portable telephone set to which a data processing apparatus is coupled, comprising means for identifying the type of the portable telephone set based on a response with respect to an operation start signal which is output to a data interface part of the portable telephone set. In this case, it is possible to positively identify the type of the portable telephone set being coupled.

A further object of the present invention is to provide a telephone set type identifying apparatus for identifying a type of portable telephone set to which a data processing apparatus

is coupled, comprising means for identifying the type of the portable telephone set based on a waveform of a signal output from a specific terminal of a data interface part of the portable telephone set. In this case, it is possible to positively identify the type of the portable telephone set immediately when the portable telephone set outputs a synchronizing signal.

Another object of the present invention is to provide a telephone set type identifying apparatus for identifying a type of portable telephone set to which a data processing apparatus is coupled, comprising means for identifying the type of the portable telephone set based on an allocation pattern of input and output terminals of a data interface part of the portable telephone set. In this case, it is possible to positively identify the type of the portable telephone set immediately when the portable telephone set is coupled.

Each of the telephone set type identifying apparatus described above may be provided within a PC card.

Still another object of the present invention is to provide a computer-readable storage medium which stores a program for causing a computer which couples to a portable telephone set to identify a type of the portable telephone set, comprising means for causing the computer to identify the type of the portable telephone set based on a response with respect to an operation start signal which is output to a data interface part of the portable telephone set. In this case, it is possible to positively identify the type of the portable telephone set being coupled.

A further object of the present invention is to provide a computer-readable storage medium which stores a program for causing a computer which

couples to a portable telephone set to identify a type of the portable telephone set, comprising means for causing the computer to identify the type of the portable telephone set based on a pattern of an asynchronous signal output from a data interface part of the portable telephone set. In this case, it is possible to positively identify the type of the portable telephone set immediately when the portable telephone set outputs a control signal.

Another object of the present invention is to provide a computer-readable storage medium which stores a program for causing a computer which couples to a portable telephone set to identify a type of the portable telephone set, comprising means for causing the computer to identify the type of the portable telephone set based on an allocation pattern of input and output terminals of a data interface part of the portable telephone set. In this case, it is possible to positively identify the type of the portable telephone set immediately when the portable telephone set is coupled.

Therefore, according to the present invention, it is possible to automatically identify the type of portable telephone set which is coupled to the data processing apparatus, so that the user does not need to be aware of the type of portable telephone set being coupled, and to realize an inexpensive DCE by making it possible to use a DCE having the same construction regardless of the type of the portable telephone set and to eliminate the need for a troublesome operation by the user so as to greatly reduce the load on the user.

Still another object of the present invention is to provide a processing apparatus operatively coupled between a communication equipment and an information processing apparatus, comprising an identifying part identifying a type of

the communication equipment and outputting an identification signal, and a switching part switching a communication protocol prestored for each type of the communication equipment, based on
5 the identification signal.

Other objects and further features of the present invention will be apparent from the following detailed description when read in conjunction with the accompanying drawings.

10

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a diagram showing the construction of a system applied with a first embodiment of a telephone set identifying method
15 according to the present invention;

FIG. 2 is a perspective view showing the general construction of a personal computer;

FIG. 3 is a system block diagram showing the general construction of a DCE;

20 FIG. 4 is a system block diagram showing the general construction of a portable telephone set;

FIG. 5 is a diagram showing an allocation pattern of input and output terminals of a connector
25 for a case where the portable telephone set is a mobile telephone set;

FIG. 6 is a diagram showing an allocation pattern of input and output terminals of a connector for a case where the portable telephone set is a PHS
30 telephone set;

FIG. 7 is a diagram showing an important part of a connection part;

FIG. 8 is a flow chart for explaining the operation of a CPU of the DCE in the first
35 embodiment of the telephone set identifying method according to the present invention;

FIG. 9 is a diagram schematically showing

a switching of programs in the first embodiment of the telephone set identifying method;

FIG. 10 is a flow chart for explaining the operation of the CPU of the DCE in a second
5 embodiment of the telephone set identifying method according to the present invention;

FIG. 11 is a flow chart for explaining the operation of the CPU of the DCE in a third
10 embodiment of the telephone set identifying method according to the present invention;

FIG. 12 is a diagram showing a synchronizing signal;

FIG. 13 is a flow chart for explaining the operation of the CPU of the DCE in a fourth
15 embodiment of the telephone set identifying method according to the present invention;

FIG. 14 is a flow chart for explaining the operation of the CPU of the DCE in a fifth
20 embodiment of the telephone set identifying method according to the present invention;

FIG. 15 is a diagram showing ground and open-circuit pins allocated to the connector, with respect to the mobile telephone set and the PHS telephone set;

FIGS. 16A and 16B respectively are
25 diagrams showing a frame signal;

FIG. 17 is a flow chart for explaining the operation of the CPU of the DCE in a sixth
30 embodiment of the telephone set identifying method according to the present invention;

FIG. 18 is a diagram showing a notification of the type of portable telephone set identified in the DCE to the personal computer;

FIG. 19 is a diagram for explaining the
35 notification of the type of portable telephone set identified in the DCE to the personal computer;

FIG. 20 is a system block diagram showing

660667 6633360

the general construction of a main body part of the personal computer which uses an embodiment of a storage medium according to the present invention;

FIG. 21 is a diagram showing a bus interface part shown in FIG. 20; and

FIG. 22 is a diagram showing the general structure of a software architecture of the personal computer.

10 DESCRIPTION OF THE PREFERRED EMBODIMENTS

A description will hereinafter be given of embodiments of the present invention, by referring to the drawings.

First, a description will be given of a first embodiment of a telephone set identifying method according to the present invention. This first embodiment of the telephone set identifying method uses a first embodiment of a telephone set type identifying apparatus according to the present invention.

FIG. 1 is a diagram showing the construction of a system which is applied with the first embodiment of the telephone set identifying method. The system shown in FIG. 1 includes a personal computer (or a computer system) 1 which is provided as a data processing apparatus, a DCE 2 which forms the telephone set type identifying apparatus, and a portable telephone set 3. In this embodiment, the DCE 2 is provided as an adapter, and includes a PC card interface and a serial interface such as RS232C.

As shown in FIG. 2, the personal computer 1 generally includes a main body part 101 which includes a central processing unit (CPU), a disk drive unit and the like, a display 102 having a display screen 102a which displays an image in response to an instruction from the main body part

101, a keyboard 103 which is used to input various
information to the personal computer 1, a mouse 104
which is used to specify an arbitrary position on
the display screen 102a of the display 102, and a
5 modem 105 which downloads an external database or
the like via the portable telephone set 3 and the
DCE 2 shown in FIG. 1 or, via another line or the
like.

A program which is executed by the CPU of
10 the personal computer 1 may be preinstalled in a
disk within the disk drive unit or the like.
Alternatively, the program may be stored in a
portable recording medium such as a disk 110 and be
installed therefrom or, the program may be
15 downloaded from another computer or the like using a
communication function such as the modem 105.

The DCE 2 includes a connector 21, a CPU
22, a ROM 23, a RAM 24, an input and output (I/O)
control part 25, a connection part 26, and a 16-pin
20 connector 29 which are connected as shown in FIG. 3.
This DCE 2 is built into a PC card which is inserted
into a lap-top personal computer or into an adapter
which is connected to a desk-top personal computer.
For example, the connector 21 is connected via a
25 cable 4 shown in FIG. 1 to RS232C terminals of the
main body part 101 of the personal computer 1 which
forms a data terminal equipment (DTE) or, is
connected directly to a PC card slot of a portable
terminal equipment such as the lap-top personal
30 computer. The CPU 22 is provided to control the
general operation of the DCE 2, and has a function
of controlling a communication protocol of the
portable telephone set 3 such as the mobile
telephone set and the PHS telephone set. A program
35 which is executed by the CPU 22 is stored in the ROM
23. In addition, the RAM 24 stores various data
including intermediate data which are obtained

during computation processes carried out by the CPU 22. The I/O control part 25 is provided to control the input to and the output from the DCE 2. The connection part 26 is provided to identify the type of the portable telephone set 3 which is coupled. The connector 29 connects to the portable telephone set 3 via a cable 5 shown in FIG. 1.

The portable telephone set 3 includes a 16-pin connector 31, a CPU 32, a ROM 33, a RAM 34, an I/O control part 35, a radio transmitter/receiver part 36, and an antenna 37 which are connected as shown in FIG. 4. The CPU 32 is provided to control the general operation of the portable telephone set 3. A program which is executed by the CPU 32 is stored in the ROM 33. In addition, the RAM 34 stores various data including intermediate data obtained during computation processes carried out by the CPU 32. The I/O control part 35 is provided to control the input to and the output from the portable telephone set 3. The radio transmitter/-receiver part 36 has a known construction including a transmitter for making a transmission via the antenna 37 and a receiver for making a reception via the antenna 37.

The basic construction of the portable telephone set 3 shown in FIG. 4 is the same for the mobile telephone set and the PHS telephone set, however, the program executed by the CPU 32 differs depending on the connection system and the communication protocol used. In addition, the construction of the connector 31 forming a data interface part may be the same for the mobile telephone set and the PHS telephone set, but an allocation pattern of input and output terminals of the connector 31 is in general different for the mobile telephone set and the PHS telephone set. A portable telephone set having a known construction,

that is, a known mobile telephone set and a known PHS telephone set may be used as the portable telephone set 3, and the construction of the portable telephone set 3 is of course not limited to the construction shown in FIG. 4.

FIG. 5 is a diagram showing an allocation pattern of the input and output terminals of the connector 31 for the case where the portable telephone set 3 is a mobile telephone set. On the other hand, FIG. 6 is a diagram showing an allocation pattern of the input and output terminals of the connector 31 for the case where the portable telephone set 3 is a PHS telephone set. In FIGS. 5 and 6, the pin number of the input and output terminals is indicated on the left side, and the signal attribute corresponding to each pin number is indicated on the right side. In FIGS. 5 and 6, GND indicates the ground, OPEN indicates an open-circuit, TCH indicates an information transmission channel for transferring communication data (real data), ADP indicates an adapter, that is, the DCE 2, and CRC indicates a cyclic redundancy check.

The construction of the connector 31 is of course not limited to the construction shown in FIGS. 5 and 6. In addition, the connector 31 is not limited to the 16-pin connector, and the connector 31 may have an arbitrary number of pins.

FIG. 7 is a diagram showing an important part of the connection part 26 of this embodiment. In FIG. 7, the numbers assigned to the pins of the connector 29 are the same as the pin numbers assigned to the connector 31 shown in FIGS. 5 and 6. The connection part 26 includes a switch 261 which is connected to ports "a" through "i" of the CPU 22 and connects to the pin numbers "1" through "16" of the connector 29. In this embodiment, the switch 261 is switched by the CPU 22 so that the port "a"

connects to the pin number "1" or "2", the port "b" connects to the pin number "4", the port "c" connects to the pin number "5", the port "d" connects to the pin number "6", the port "e" connects to the pin number "7", the port "f" connects to the pin number "10", the port g connects to the pin number "3", the port "h" connects to the pin number "11", and the port "i" connects to the pin number "15". If the portable telephone set 3 being coupled is the PHS telephone set, the port "a" is connected to the pin number "1". On the other hand, the port "a" is connected to the pin number "2" if the portable telephone set 3 being coupled is the mobile telephone set. For example, the switching of the switch 261 may be set by the CPU 22 depending on the type of the portable telephone set 3 used or, may be set fixedly. In FIG. 7, the pin allocation is shown on the right side in correspondence with each of the pin numbers "1" through "16" of the connector 29 for both cases where the portable telephone set 3 is the mobile telephone set and the portable telephone set 3 is the PHS telephone set.

FIG. 8 is a flow chart for explaining the operation of the CPU 22 of the DCE 2 of this embodiment. When an operation start signal from the portable telephone set 3 is input to the port "h" or the port "i" of the CPU 22 to generate an interrupt, the process shown in FIG. 8 is called. In FIG. 8, a step S1 decides whether the operation start signal output from the portable telephone set 3 which is coupled to the DCE 2 is received at the port "h" or the port "i" of the CPU 22 via the connector 31, the cable 5, the connector 29 and the connection part 26. If an ADP power supply control signal is received by the port "i" as the operation start signal, a step Sa sets information which indicates the type of the

portable telephone set 3 as the mobile telephone set.
On the other hand, if an ADP sleep mode cancel
signal is received by the port "h" as the operation
start signal, a step S3 sets information which
5 indicates the type of the portable telephone set 3
as the PHS telephone set. After the step S2 or S3,
a step S4 issues a telephone set type primitive, so
as to notify the identified type of the portable
telephone set 3 to the personal computer 1 via the
10 I/O control part 25, the connector 21 and the cable
4, and the process ends.

FIG. 9 is a diagram schematically showing
the switching of control programs in this embodiment.
In FIG. 9, a control (detection) program P1 of the
15 CPU 22 identifies whether the coupled portable
telephone set 3 is a mobile telephone set or a PHS
telephone set, by carrying out the processes of the
steps S1 through S3 shown in FIG. 8. In the case
where the portable telephone set 3 is the mobile
20 telephone set as a result of this identification,
the control program of the CPU 22 is switched to a
control program P11 for the mobile telephone set,
and processes including the process of the step S4
shown in FIG. 8 are carried out. On the other hand,
25 in the case where the portable telephone set 3 is
the PHS telephone set as a result of this
identification, the control program of the CPU 22 is
switched to a control program P12 for the PHS
telephone set, and processes including the process
30 of the step S4 shown in FIG. 8 are carried out.

The switching of the control program can
be made by reading the control program P11 or P12
from a program storage region of the ROM 23. In
addition, in a case where it is necessary to switch
35 the hardware connection between the switch 261 and
the connector 29 within the connection part 26 of
the DCE 2 (that is, switch the hardware connection

of an interface between the DCE 2 and the portable telephone set 3) when the control program is switched, a control signal for switching the connection of the switch 261 is output from the CPU 22 before switching the control program. In FIG. 7, the control signal output from the CPU 22 switches the connection of the switch 261 so that the port "a" is switched and connected to the pin number "1" of the connector 29 if the identification result indicates that the portable telephone set 3 is a PHS telephone set. On the other hand, the control signal output from the CPU 22 switches the connection of the switch 261 so that the port "a" is switched and connected to the pin number "2" of the connector 29 if the identification result indicates that the portable telephone set 3 is a mobile telephone set.

Next, a description will be given of a second embodiment of the telephone set identifying method according to the present invention. This second embodiment of the telephone set identifying method uses a second embodiment of the telephone set type identifying apparatus according to the present invention. The construction of the system applied with this second embodiment of the telephone set identifying method is the same as that applied with the first embodiment of the telephone set identifying method described above in conjunction with FIG. 1, and the basic construction of each part of the system in this second embodiment is the same as the basic construction of the corresponding part used in the first embodiment.

FIG. 10 is a flow chart for explaining the operation of the CPU 22 of the DCE 2 in this second embodiment. In FIG. 10, a step S11 transmits, as an operation start signal, a PHS telephone set control signal which is included in an up-control signal,

from the port "d" shown in FIG. 7 via the switch 261 of the connection part 26. As a result, the PHS telephone control signal which is output from the connection part 26 of the DCE 2 via the pin number
5 "6" of the connector 29 is transmitted to the portable telephone set 3 via the cable 5 and the pin number "6" of the connector 31. A step S12 decides whether or not a response is received from the portable telephone set 3 which is a PHS telephone
10 set. For example, the step S12 decides whether or not a response is received from the portable telephone set 3 which is a PHS telephone set, by deciding whether or not a down-control signal from the pin number "7" of the connector 31 of the
15 portable telephone set 3 is received by the port "e" via the cable 5, the pin number "7" of the connector 29 and the switch 261 of the connection part 26.

If no response is received in the step S12, a step S13 waits for a predetermined time.
20 Thereafter, a step S14 transmits, as an operation start signal, a mobile telephone control signal which is included in an up-control signal, from the port "d" via the switch 261 of the connection part 26. Hence, the mobile telephone control signal
25 which is output from the connection part 26 of the DCE 2 via the pin number "6" of the connector 29 is transmitted to the portable telephone set 3 via the cable 5 and the pin number "6" of the connector 31. A step S15 decides whether or not a response is
30 received from the portable telephone set 3 which is a mobile telephone set. For example, the step S15 decides whether or not a response is received from the portable telephone set 3 which is a mobile telephone set, by deciding whether or not a down-
35 control signal from the pin number "7" of the connector 31 of the portable telephone set 3 is received by the port "e" via the cable 5, the pin

number "7" of the connector 29 and the switch 261 of the connection part 26. The process ends if no response is received in the step S15.

On the other hand, if a response is received in the step S12, a step S16 sets information which indicates the type of the portable telephone set 3 as the PHS telephone set. After the step S16, a step S17 issues a telephone set type primitive, so as to notify the identified type of the portable telephone set 3 to the personal computer 1 via the I/O control part 25, the connector 21 and the cable 4, and the process ends.

Further, if a response is received in the step S15, a step S18 sets information which indicates the type of the portable telephone set 3 as the mobile telephone set. After the step S18, a step S19 issues a telephone set type primitive, so as to notify the identified type of the portable telephone set 3 to the personal computer 1 via the I/O control part 25, the connector 21 and the cable 4, and the process ends.

Next, a description will be given of a third embodiment of the telephone set identifying method according to the present invention. This third embodiment of the telephone set identifying method uses a third embodiment of the telephone set type identifying apparatus according to the present invention. The construction of the system applied with this third embodiment of the telephone set identifying method is the same as that applied with the first embodiment of the telephone set identifying method described above in conjunction with FIG. 1, and the basic construction of each part of the system in this third embodiment is the same as the basic construction of the corresponding part used in the first embodiment.

FIG. 11 is a flow chart for explaining the

operation of the CPU 22 of the DCE 2 in this third embodiment. The CPU 22 has a function of receiving a synchronizing signal which is output from the portable telephone set 3 which is coupled to the DCE 2 at the port "e" of the CPU 22 via the connector 31, the cable 5, the connector 29 and the connection part 26, and counting the synchronizing signal received at the port "e". For example, this synchronizing signal is a TCH clock having a frequency of 42 kHz in the case where the portable telephone set 3 is a mobile telephone set, and is a data transmitting and receiving clock having a frequency of 32 kHz or 64 kHz in the case where the portable telephone set 3 is a PHS telephone set. As shown in FIG. 12, the CPU 22 counts the number of high levels or low levels of the synchronizing signal for a predetermined time from a timer start time to a timer stop time of the CPU 22, and the process shown in FIG. 11 is called when this counting operation of the CPU 22 ends.

A step S21 inputs a counted value of the synchronizing signal, and a step S22 decides from the input counted value whether the frequency of the counted synchronizing signal matches the frequency (42 kHz) of the mobile telephone set or matches the frequency (32 kHz or 64 kHz) of the PHS telephone set. If the frequency of the synchronizing signal is 42 kHz, a step S23 sets information which indicates the type of the portable telephone set 3 as the mobile telephone set. On the other hand, if the frequency of the synchronizing signal is 32 kHz or 64 kHz, a step S24 sets information which indicates the type of the portable telephone set 3 as the PHS telephone set. After the step S23 or S24, a step S25 issues a telephone set type primitive, so as to notify the identified type of the portable telephone set 3 to the personal computer 1 via the

I/O control part 25, the connector 21 and the cable 4, and the process ends.

Next, a description will be given of a fourth embodiment of the telephone set identifying method according to the present invention. This fourth embodiment of the telephone set identifying method uses a fourth embodiment of the telephone set type identifying apparatus according to the present invention. The construction of the system applied with this fourth embodiment of the telephone set identifying method is the same as that applied with the first embodiment of the telephone set identifying method described above in conjunction with FIG. 1, and the basic construction of each part of the system in this fourth embodiment is the same as the basic construction of the corresponding part used in the first embodiment.

FIG. 13 is a flow chart for explaining the operation of the CPU 22 of the DCE 2 in this fourth embodiment. A down-control signal which is output from the portable telephone set 3 which is coupled to the DCE 2 is received by the port "e" of the CPU 22 via the connector 31, the cable 5, the connector 29 and the connection part 26. The down-control signal includes an asynchronous signal. For example, this asynchronous signal has a bit rate of 600 bps in the case where the coupled portable telephone set 3 is a mobile telephone set, and has a bit rate of 2400 bps in the case where the coupled portable telephone set 3 is a PHS telephone set. For the sake of convenience, it is assumed that the CPU 2 is set to receive the asynchronous signal of 600 bps in the initial state. The process shown in FIG. 13 is called when a reception interrupt is generated from the portable telephone set 3.

A step S31 decides whether or not a reception error is generated in a state where the

CPU 22 is set to receive the asynchronous signal of 600 bps. If the decision result in the step S31 is YES, a step S32 switches the setting of the CPU 22 to receive the asynchronous signal of 2400 bps, and the process ends. As a result, when the reception interrupt is generated, the step S31 this time decides whether or not a reception error is generated in a state where the CPU 22 is set to receive the asynchronous signal of 2400 bps.

On the other hand, if the decision result in the step S31 becomes NO, a step S33 decides whether the bit rate of the asynchronous signal presently being received is 600 bps or 2400 bps. If the bit rate of the asynchronous signal being received is 600 bps, a step S34 sets information which indicates the type of the portable telephone set 3 as the mobile telephone set. If the bit rate of the asynchronous signal being received is 2400 bps, a step S35 sets information which indicates the type of the portable telephone set 3 as the PHS telephone set. After the step S34 or S35, a step S36 issues a telephone set type primitive, so as to notify the identified type of the portable telephone set 3 to the personal computer 1 via the I/O control part 25, the connector 21 and the cable 4, and the process ends.

Next, a description will be given of a fifth embodiment of the telephone set identifying method according to the present invention. This fifth embodiment of the telephone set identifying method uses a fifth embodiment of the telephone set type identifying apparatus according to the present invention. The construction of the system applied with this fifth embodiment of the telephone set identifying method is the same as that applied with the first embodiment of the telephone set identifying method described above in conjunction

with FIG. 1, and the basic construction of each part of the system in this fifth embodiment is the same as the basic construction of the corresponding part used in the first embodiment.

5 FIG. 14 is a flow chart for explaining the operation of the CPU 22 of the DCE 2 in this fifth embodiment. As described above in conjunction with FIGS. 5 through 7, the ground pins and the open pins allocated to the connectors 31 and 29 are different
10 for the case where the coupled portable telephone set 3 is a mobile telephone set and the case where the coupled portable telephone set 3 is a PHS telephone set. FIG. 15 is a diagram showing the ground pins and the open pins allocated to the
15 connector 29, with respect to the mobile telephone set and the PHS telephone set. In FIG. 15, "G" denotes the ground, "O" denotes the open-circuit, and "-" indicates neither the ground nor the open-circuit. In this embodiment, the combination of the
20 pin numbers of the ground pins of the connector 29 detected by the CPU 22 is compared with the combinations shown FIG. 15, so as to determine whether the coupled portable telephone set 3 is a mobile telephone set or a PHS telephone set.

25 A step S41 decides whether the coupled portable telephone set 3 is a mobile telephone set or a PHS telephone set, by comparing the combination of the pin numbers of the ground pins of the connector 29 detected by the CPU 22 with the
30 combinations shown in FIG. 15. For example, if the combination of the pin numbers of the ground pins of the connector 29 detected by the CPU 22 is "1", "3", "9" and "14", it is judged that the coupled portable telephone set 3 is a mobile telephone set. If the
35 step S41 decides that the coupled portable telephone set 3 is a mobile telephone set, a step S42 sets information which indicates the type of the portable

telephone set 3 as the mobile telephone set. On the other hand, if the step S41 decides that the coupled portable telephone set 3 is a PHS telephone set, a step S43 sets information which indicates the type of the portable telephone set 3 as the PHS telephone set. After the step S42 or S43, a step S44 issues a telephone set type primitive, so as to notify the identified type of the portable telephone set 3 to the personal computer 1 via the I/O control part 25, the connector 21 and the cable 4, and the process ends.

Next, a description will be given of a sixth embodiment of the telephone set identifying method according to the present invention. This sixth embodiment of the telephone set identifying method uses a sixth embodiment of the telephone set type identifying apparatus according to the present invention. The construction of the system applied with this sixth embodiment of the telephone set identifying method is the same as that applied with the first embodiment of the telephone set identifying method described above in conjunction with FIG. 1, and the basic construction of each part of the system in this sixth embodiment is the same as the basic construction of the corresponding part used in the first embodiment.

FIG. 17 is a flow chart for explaining the operation of the CPU 22 of the DCE 2 in this sixth embodiment. As shown in FIGS. 16A and 16B, the frequency of a frame signal used in the portable telephone set 3 is different between the mobile telephone set and the PHS telephone set. FIG. 16A shows a TCH frame signal having a frequency of 50 Hz which is used as the frame signal in the mobile telephone set, and FIG. 16B shows a down-frame clock having a frequency of 200 Hz which is used as the frame signal in the PHS telephone set. In this

embodiment, the CPU 22 detects the frequency of the frame signal received from the portable telephone set 3, so as to judge whether the coupled portable telephone set 3 is a mobile telephone set or a PHS telephone set.

The frame signal which is output from the portable telephone set 3 which is coupled to the DCE 2, is received at the port "b" of the CPU 22 via the connector 31, the cable 5, the connector 29 and the connection part 26. A step S51 detects the frequency of the frame signal received at the port "b". A step S52 decides whether the detected frequency of the frame signal is 50 Hz corresponding to the mobile telephone set or 200 Hz corresponding to the PHS telephone set. If the frequency of the frame signal detected in the step S52 is 50 Hz, the received frame signal is a TCH frame signal from a mobile telephone set, and it is judged that the coupled portable telephone set 3 is the mobile telephone set. In this case, a step S53 sets information which indicates the type of the portable telephone set 3 as the mobile telephone set. On the other hand, if the frequency of the frame signal detected in the step S52 is 200 Hz corresponding to the PHS telephone set, the received frame signal is a down-frame clock from a PHS telephone set, and it is judged that the coupled portable telephone set 3 is the PHS telephone set. In this case, a step S54 sets information which indicates the type of the portable telephone set 3 as the PHS telephone set. After the step S53 or S54, a step S55 issues a telephone set type primitive, so as to notify the identified type of the portable telephone set 3 to the personal computer 1 via the I/O control part 25, the connector 21 and the cable 4, and the process ends.

In each of the embodiments described above,

the type of the portable telephone set 3 identified by the DCE 2 can be notified using a serial line coupled to the personal computer 1, by use of the cable 4. FIG. 18 is a diagram showing the

5 notification of the type of the portable telephone set 3 identified by the DCE 2 to the personal computer 1. In FIG. 18, when the portable telephone set 3 is coupled to the DCE 2 and the DCE 2 identifies the type of the portable telephone set 3,

10 a character indication "PHONE: 1", for example, is output to the serial line so as to notify the identified type of the portable telephone set 3 to the personal computer 1. Accordingly, at the

15 of the coupled portable telephone set 3 from the notified character indication. For example, the personal computer 1 can carry out processes, such as making a communication process between a

20 communication application in a higher level or layer, by switching a communication controlling software which controls the communication depending on the type of the portable telephone set 3.

In other words, when the personal computer 1 is notified of the type of the portable telephone set 3 identified by the DCE 2 in FIG. 19, an

25 operating system OP1 of the personal computer 1 can know the type of the portable telephone set 3 which is coupled to the personal computer 1 via the DCE 2. In a case where the type of the portable telephone

30 set 3 is the mobile telephone set, the communication controlling software which controls the communication depending on the type of the portable telephone set 3 is switched to a communication

35 controlling application apl. On the other hand, in a case where the type of the portable telephone set 3 is the PHS telephone set, the communication controlling software which controls the

communication depending on the type of the portable telephone set 3 is switched to a communication controlling application ap2. Accordingly, at the personal computer 1, it is possible to carry out processes such as making a communication process between the communication controlling application ap1 or ap2 depending on the type of the coupled portable telephone set 3 and a communication application APL1 in a higher level or layer.

Next, a description will be given of an embodiment of a computer-readable storage medium according to the present invention. In each of the embodiments described above, the DCE 2 is provided independently of the personal computer 1. However, the functions of the DCE 2 may be provided within the personal computer 1. In this case, the DCE 2 is mounted on a PC card or the like, and the DCE 2 may be detachably provided with respect to the main body part 101 of the personal computer 1 or, the DCE 2 may be fixedly provided in the main body part 101 of the personal computer 1. On the other hand, the functions of the DCE 2 may be realized by the CPU within the personal computer 1. Accordingly, this embodiment of the storage medium may be formed by a storage medium which stores a program which is executed by the CPU 22 within the DCE 2 or, a storage medium which stores a program which is executed by the CPU which is provided within the personal computer 1 and realizes the functions of the DCE 2. In the following description, it is assumed for the sake of convenience that the storage medium stores a program which is executed by the CPU which is provided within the personal computer 1 and realizes the functions of the DCE 2.

The storage medium is not limited to a portable storage medium such as integrated circuit (IC) card memories, floppy disks, magneto-optical

disks and CD-ROMs, and includes storage mediums which are accessible by a computer system which is coupled via a communication means or a communication unit such as a modem, LAN and the like.

5 FIG. 20 is a system block diagram showing the general construction of the main body part 101 of the personal computer 1 which uses this embodiment of the storage medium. The personal computer 101 includes a CPU 11, a hard disk drive (HDD) 12, a ROM 14, a disk unit 15 and an ASIC communication LSI 16 which are coupled via a bus 19 as shown in FIG. 20, and a hard disk 13 which is driven by the HDD 12. A connector 17 which corresponds to the connector 29 is connected to the communication LSI 16. As shown in FIG. 21, this connector 17 is coupled to the connector 31 of the portable telephone set 3 via the cable 5. The communication LSI 16 includes a communication function (asynchronous serial control and synchronous serial control) of the personal computer 101, and a function of controlling the I/O ports. The communication LSI 16 forms a PCI or an ISA bus interface, for example, with respect to the bus 19 of the personal computer 1.

25 For example, this embodiment of the storage medium is formed by the disk 110 shown in FIG. 2, and stores a program for realizing one of the first through sixth embodiments of the telephone set identifying method described above or, an arbitrary combination of the first through sixth embodiments of the telephone set identifying method described above. The program which is read from the disk 110 by the disk unit 15 is installed, for example, in the hard disk 13 via the HDD 12, under the control of the CPU 11. Hence, the CPU 11 carries out one of or an arbitrary combination of the processes described above in conjunction with

FIGS. 8, 10, 11, 13, 14 and 17, so as to identify the type of the portable telephone set 3 which is coupled to the personal computer 1. In this case, the type of the portable telephone set 3 is
5 identified within the personal computer 1, and thus, in this embodiment, the step of notifying the identified type of the portable telephone set 3 to the personal computer 1 in each of the first through sixth embodiments notifies the identified type to an
10 operating system or an application having a higher level or layer.

FIG. 22 is a diagram showing the general structure of a software architecture of the personal computer 1. Various applications and drivers shown
15 in FIG. 22 are provided under the operating system OP shown in FIG. 19. A personal computer communication application 603, an asynchronous PPP driver 602 and a TCP/IP communication application 601 such as a browser, are respectively provided as
20 application in the higher level or layer, with respect to a communication port driver 604, and carry out various kinds of communication control. The communication port driver 604 is provided as an application in a higher level or layer, with respect
25 to a pseudo serial driver group 605, and carries out various kinds of port driver control. The pseudo serial driver group 605 includes a communication controlling application (mobile telephone driver) ap1 which controls the communication for a mobile
30 telephone set when the coupled portable telephone set 3 is the mobile telephone set, a communication controlling application (PHS telephone driver) ap2 which controls the communication for a PHS telephone set when the coupled portable telephone set 3 is the
35 PHS telephone set, and an identifying application (identification driver) ap3 which identifies the type of the coupled portable telephone set 3. The

program stored in this embodiment of the storage medium includes at least the identifying application (identification driver) ap3. The pseudo serial driver group 605 can communicate with the portable telephone set 3 via the communication LSI 16 shown in FIG. 21.

Therefore, this embodiment of the storage medium can provide a driver such as the identifying application (identification driver) ap3, with respect to an application in the higher level or layer such as the communication port driver 604.

It is conceivable to construct a DCE apparatus which is provided with both a DCE designed exclusively for the mobile telephone set and a DCE designed exclusively for the PHS telephone set. But in this case, the hardware construction becomes complex, and it becomes difficult to reduce both the size and cost of the DCE apparatus. On the other hand, according to the present invention, the hardware used is the same regardless of the type of the portable telephone set, and the required process with respect to the mobile telephone set or the PHS telephone set is carried out by automatically identifying the type of the portable telephone set and switching the software. For this reason, the present invention does not require a complex hardware, and it is possible to easily reduce both the size and the cost of the telephone set type identifying apparatus.

In addition, the shape of the connector used in the conventional portable telephone set is different depending on the type of the portable telephone set, in order to prevent the user from making an erroneous connection. Hence, although the number of pins used are the same for the connectors, connectors having various different shapes had to be manufactured and used for the corresponding types of

portable telephone sets. However, if it is possible to use connectors having the same shape regardless of the types of portable telephone sets, it would substantially simplify matters and also considerably
5 reduce the cost of the connectors. In the present invention, it is possible to automatically identify and recognize within the DCE or within the personal computer, the type of the portable telephone set which is coupled to the DCE, and thus, the user does
10 not need to be aware of the type of the portable telephone set which is to be coupled to the DCE. Therefore, no inconveniences are introduced in the present invention even if connectors having the same shape are used regardless of the type of the
15 portable telephone sets.

Further, the present invention is not limited to these embodiments, but various variations and modifications may be made without departing from the scope of the present invention.

20

25

30

35

WHAT IS CLAIMED IS

5

1. A telephone set identifying method for identifying a type of portable telephone set to which a data processing apparatus is coupled, comprising the steps of:

10

identifying the type of the portable telephone set based on a response with respect to an operation start signal which is output to a data interface part of the portable telephone set.

15

2. A telephone set identifying method for identifying a type of portable telephone set to which a data processing apparatus is coupled, comprising the steps of:

20

identifying the type of the portable telephone set based on a waveform of a signal output from a specific terminal of a data interface part of the portable telephone set.

25

30

3. A telephone set identifying method for identifying a type of portable telephone set to which a data processing apparatus is coupled, comprising the steps of:

35

identifying the type of the portable telephone set based on an allocation pattern of input and output terminals of a data interface part of the portable telephone set.

4. A telephone set type identifying apparatus for identifying a type of portable telephone set to which a data processing apparatus is coupled, comprising:

5 means for identifying the type of the portable telephone set based on a response with respect to an operation start signal which is output to a data interface part of the portable telephone set.

10

5. A telephone set type identifying apparatus for identifying a type of portable
15 telephone set to which a data processing apparatus is coupled, comprising:

means for identifying the type of the portable telephone set based on a waveform of a signal output from a specific terminal of a data interface part of
20 the portable telephone set.

25 6. A telephone set type identifying apparatus for identifying a type of portable telephone set to which a data processing apparatus is coupled, comprising:

means for identifying the type of the portable
30 telephone set based on an allocation pattern of input and output terminals of a data interface part of the portable telephone set.

35

7. A PC card comprising:

a telephone set type identifying apparatus
identifying a type of portable telephone set to
which a data processing apparatus is coupled,

5 said telephone set type identifying apparatus
comprising:

 means for identifying the type of the
portable telephone set based on a response with
respect to an operation start signal which is output
to a data interface part of the portable telephone
10 set.

15 8. A PC card comprising:

a telephone set type identifying apparatus
identifying a type of portable telephone set to
which a data processing apparatus is coupled,

20 said telephone set type identifying apparatus
comprising:

 means for identifying the type of the
portable telephone set based on a waveform of a
signal output from a specific terminal of a data
interface part of the portable telephone set.

25

 9. A PC card comprising:

30 a telephone set type identifying apparatus
identifying a type of portable telephone set to
which a data processing apparatus is coupled,

 said telephone set type identifying apparatus
comprising:

35 means for identifying the type of the portable
telephone set based on an allocation pattern of
input and output terminals of a data interface part

of the portable telephone set.

5

10. A computer-readable storage medium which stores a program for causing a computer which couples to a portable telephone set to identify a type of the portable telephone set, comprising:

10 means for causing the computer to identify the type of the portable telephone set based on a response with respect to an operation start signal which is output to a data interface part of the portable telephone set.

15

11. A computer-readable storage medium which stores a program for causing a computer which couples to a portable telephone set to identify a type of the portable telephone set, comprising:

20 means for causing the computer to identify the type of the portable telephone set based on a pattern of an asynchronous signal output from a data interface part of the portable telephone set.

30

12. A computer-readable storage medium which stores a program for causing a computer which couples to a portable telephone set to identify a type of the portable telephone set, comprising:

35 means for causing the computer to identify the type of the portable telephone set based on an allocation pattern of input and output terminals of

a data interface part of the portable telephone set.

5

13. A processing apparatus operatively coupled between a communication equipment and an information processing apparatus, comprising:

10 an identifying part identifying a type of the communication equipment and outputting an identification signal; and

15 a switching part switching a communication protocol prestored for each type of the communication equipment, based on the identification signal.

20

14. The processing apparatus as claimed in claim 13, wherein the communication equipment is a mobile communication equipment.

25

15. The processing apparatus as claimed in claim 14, wherein the mobile communication is a mobile telephone set capable of making a
30 communication while moving or a personal handy-phone system telephone set unsuited for making a communication while moving.

35

ABSTRACT OF THE DISCLOSURE

The telephone set type identifying
apparatus is constructed so that a type of a
portable telephone set is identified and notified to
5 a data processing apparatus, based on a signal which
is received from a data interface part of the
portable telephone set which is coupled to the data
processing apparatus or based on an allocation
pattern of input and output terminals of the data
10 interface part of the portable telephone set.

15

20

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5

PIN NUMBER	SIGNAL ATTRIBUTE
①	GND
②	TCH TRANSMITTING SIGNAL
③	GND
④	TCH FRAME SIGNAL
⑤	TCH CLOCK
⑥	UP-CONTROL SIGNAL
⑦	DOWN-CONTROL SIGNAL
⑧	OPEN
⑨	GND
⑩	TCH RECEIVING SIGNAL
⑪	OPEN
⑫	PORTABLE SET OPERATION CONTROL SIGNAL
⑬	PORTABLE SET OPERATION CONTROL SIGNAL
⑭	GND
⑮	ADP POWER SUPPLY CONTROL
⑯	OPEN

FIG. 6

PIN NUMBER	SIGNAL ATTRIBUTE
①	UP 32K BEARER SIGNAL
②	GND
③	OPEN
④	DOWN-FRAME CLOCK
⑤	DATA TRANSMITTING/RECEIVING CLOCK
⑥	UP-CONTROL SIGNAL
⑦	DOWN-CONTROL SIGNAL
⑧	OPEN
⑨	GND
⑩	DOWN 32K BEARER SIGNAL
⑪	ADP SLEEP MODE CANCEL SIGNAL
⑫	CRC
⑬	UP-FRAME CLOCK
⑭	ADP READY SIGNAL
⑮	PHS SLEEP CANCEL SIGNAL
⑯	OPEN

FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 13




FIG. 14




FIG. 15

PIN NUMBER	1	2	3	8	9	11	14	16
MOBILE TEL.	G	—	G	O	G	O	G	O
PHS TEL.	—	G	O	O	G	—	—	O

G : GND
O : OPEN

FIG. 16A

MOBILE TEL. (TCH FRAME SIGNAL)




FIG. 16B

PHS TEL. (DOWN-FRAME CLOCK)




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21





FIG. 22



Declaration and Power of Attorney for U.S. Patent Application

特許出願宣言書及び委任状

Japanese Language Declaration

日本語宣言書

下記の氏名の発明者として、私は以下の通り宣言します。

As a below named inventor, I hereby declare that:

私の住所、私書箱、国籍は下記の私の氏名の後に記載された通りです。

My residence, post office address and citizenship are as stated next to my name.

下記の名称の発明に関して請求範囲に記載され、特許出願している発明内容について、私が最初かつ唯一の発明者（下記の氏名が一つの場合）もしくは最初かつ共同発明者であると（下記の名称が複数の場合）信じています。

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

TELEPHONE SET IDENTIFYING METHOD,TELEPHONE SET TYPE IDENTIFYING APPARATUS,PROCESSING APPARATUS AND STORAGE MEDIUM

上記発明の明細書（下記の欄でx印がついていない場合は、本書に添付）は、

the specification of which is attached hereto unless the following box is checked:

☐ 月 日に提出され、米国出願番号または特許協定条約国際出願番号を _____ とし、
(該当する場合) _____ に訂正されました。☐ was filed on _____
as United States Application Number or
PCT International Application Number
_____ and was amended on
_____ (if applicable).

私は、特許請求範囲を含む上記訂正後の明細書を検討し、内容を理解していることをここに表明します。

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、連邦規則法典第37編第1条56項に定義されたとおり、特許資格の有無について重要な情報を開示する義務があることを認めます。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

Japanese Language Declaration (日本語宣言書)

私は、米国法典第35編119条(a)-(d)項又は365条(b)項に基づき下記の、米 国以外の国の少なくとも一カ国を指定している特許協力条約 365 (a) 項に基づく国際出願、又は外国での特許出願もしくは発明者証の出願についての外国優先権をここに主張するとともに、優先権を主張している、本出願の前に出願された特許または発明者証の外国出願を以下に、枠内をマークすることで、示しています。

Prior Foreign Application(s) (Patent Application)

外国での先行出願
No.10-115507

(Number)
(番号)

Japan

(Country)
(国名)

24/April/1998

(Day/Month/Year Filed)
(出願年月日)

Priority Not Claimed
優先権主張なし

☐

(Number)
(番号)

(Country)
(国名)

(Day/Month/Year Filed)
(出願年月日)

☐

私は、第35編米国法典119条(e)項に基づいて下記の米 国特許出願規定に記載された権利をここに主張いたします。

(Application No.)
(出願番号)

(Filing Date)
(出願日)

(Application No.)
(出願番号)

(Filing Date)
(出願日)

私は、下記の米国法典第35編120条に基づいて下記の米 国特許出願に記載された権利、又は米 国を指定している特許協力条約365条(c)に基づき権利をここに主張します。また、本出願の各請求範囲の内容が米国法典第35編112条第1項又は特許協力条約で規定された方法で先行する米 国特許出願に開示されていない限り、その先行米 国出願書提出日以降で本出願書の日本国内または特許協力条約国際提出日までの期間中に入手された、連邦規則法典第37編1条56項で定義された特許資格の有無に関する重要な情報について開示義務があることを認識しています。

(Application No.)
(出願番号)

(Filing Date)
(出願日)

(Status: Patented, Pending, Abandoned)
(現況: 特許許可済、係属中、放棄済)

(Application No.)
(出願番号)

(Filing Date)
(出願日)

(Status: Patented, Pending, Abandoned)
(現況: 特許許可済、係属中、放棄済)

私は、私自身の知識に基づいて本宣言書で私が行なう表明が真実であり、かつ私の入手した情報と私の信じることに基づき表明が全て真実であると信じていること、さらに故意になされた虚偽の表明及びそれと同等の行為は米国法典第18編第1001条に基づき、罰金または拘禁、もしくはその両方により処罰されること、そしてそのような故意による虚偽の声明を行なえば、出願した、又は既に許可された特許の有効性が失われることを認識し、よってここに上記のごとく宣誓を致します。

I hereby claim foreign priority under Title 35, United States Code, Section 119 (a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of application.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Japanese Language Declaration
(日本語宣言書)

委任状： 私は下記の発明者として、本出願に関する一切の
手続きを米特許商標局に対して遂行する弁理士または代理人
として、下記の者を指名いたします。（弁理士、または代理人
の氏名及び登録番号を明記のこと）

POWER OF ATTORNEY: As a named inventor, I hereby appoint
the following attorney(s) and/or agent(s) to prosecute this
application and transact all business in the Patent and Trademark
Office connected therewith (list name and registration number)
See list of attorneys and/or agents on page 5.

書類送付先

Send Correspondence to:

ARMSTRONG, WESTERMAN, HATTORI,
McLELAND & NAUGHTON
1725 K Street, N.W., Suite 1000
Washington, D.C. 20006

直接電話連絡先：（名前及び電話番号）

Direct Telephone Calls to: (name and telephone number)

Telephone: (202) 659-2930 Fax: (202) 887-0357

唯一または第一発明者名	Full name of sole or first inventor Takahiro Matsumura		
発明者の署名	日付	Inventor's signature	Date March 23, 1999
住所	Residence Kawasaki-shi, Kanagawa, Japan		
国籍	Citizenship Japan		
私書箱	Post Office Address C/O FUJITSU LIMITED, 1-1, Kamikodanaka 4-chome, Nakahara-ku, Kawasaki-shi, Kanagawa, 211-8588 Japan		
第二共同発明者	Full name of second joint inventor, if any		
第二共同発明者	日付	Second inventor's signature	Date
住所	Residence		
国籍	Citizenship		
私書箱	Post Office Address		

（第三以降の共同発明者についても同様に記載し、署名をす
ること）

(Supply similar information and signature for third and subsequent
joint inventors.)

第三共同発明者		Full name of third joint inventor, if any	
第三発明者の署名	日付	Third inventor's signature	Date
住所		Residence	
国籍		Citizenship	
私書箱		Post Office Address	
第四共同発明者		Full name of fourth joint inventor, if any	
第四発明者の署名	日付	Fourth inventor's signature	Date
住所		Residence	
国籍		Citizenship	
私書箱		Post Office Address	
第五共同発明者		Full name of fifth joint inventor, if any	
第五発明者の署名	日付	Fifth inventor's signature	Date
住所		Residence	
国籍		Citizenship	
私書箱		Post Office Address	
第六共同発明者		Full name of sixth joint inventor, if any	
第六発明者の署名	日付	Sixth inventor's signature	Date
住所		Residence	
国籍		Citizenship	
私書箱		Post Office Address	

List of attorneys and/or agents

James E. Armstrong, III, Reg. No. 18,366; William F. Westerman, Reg. No. 29,988; Ken-Ichi Hattori, Reg. No. 32,861; Le-Nhung McLeland, Reg. No. 31,541; Ronald F. Naughton, Reg. No. 24,616; John R. Pegan, Reg. No. 18,069; William G. Kratz, Jr., Reg. No. 22,631; James P. Welch, Reg. No. 17,379; Albert Tockman, Reg. No. 19,722; Mel R. Quintos, Reg. No. 31,898; Donald W. Hanson, Reg. No. 27,133; Stephen G. Adrian, Reg. No. 32,878; William L. Brooks, Reg. No. 34,129; John F. Carney, Reg. No. 20,276; Edward F. Welsh, Reg. No. 22,455; Patrick D. Muir, Reg. No. 37,403; Gay A. Spahn, Reg. No. 34,978; John P. Kong, Reg. No. 40,054; and Luke A. Kilyk, Reg. No. 33,251.